

4 3/4" X-series AST

Bottomhole assembly: The AST tool is generally placed in the BHA above the non-magnetic part of the BHA. Contact your Tomax representative for advice on AST placement in the BHA.

Drilling: The X-Series AST is designed with a working range covering all conventional operations, including combination with Under-Reamer. No particular steps are required when drilling with the AST. A User Manual is provided with every deployment.

TOOL SPECIFICATIONS:

PARAMETER	METRIC	IMPERIAL
<i>Length</i>	<i>5.49 m</i>	<i>18.01 ft</i>
<i>Stroke</i>	<i>0.25 m</i>	<i>10"</i>
<i>Max. OD</i>	<i>121 mm</i>	<i>4.75"</i>
<i>Min. ID</i>	<i>35 mm</i>	<i>1.38"</i>
<i>Mass</i>	<i>363 kg</i>	<i>800 lbs</i>
<i>Max. RPM</i>	<i>As recommended from bit manufacturer</i>	<i>As recommended from bit manufacturer</i>
<i>Ultimate tensile load</i>	<i>180 kdaN</i>	<i>400 klbs</i>
<i>Max. diff. pressure</i>	<i>690 bar</i>	<i>10 000 psi</i>
<i>Max. hydrostatic pressure</i>	<i>2000 bar (balanced)</i>	<i>30 000 psi (balanced)</i>
<i>Max. sand content</i>	<i>1 %</i>	<i>1 %</i>
<i>Max. DLS</i>	<i>25 deg/30 m</i>	<i>25 deg/100 ft</i>
<i>Max. temp. operational</i>	<i>200 °C (XT 220 °C)</i>	<i>390 °F (XT 425 °F)</i>
<i>Connection top</i>	<i>NC 38 box</i>	<i>NC 38 box</i>
<i>Make up torque</i>	<i>13 300 Nm</i>	<i>9 800 ftlbs</i>
<i>Connection bottom</i>	<i>NC 38 pin</i>	<i>NC 38 pin</i>
<i>Make up torque</i>	<i>13 300 Nm</i>	<i>9 800 ftlbs</i>

Patented in key countries world wide

Configurations: XT = High temp. (220 °C)

